

DIGITUS 1.25 Gbps copper SFP-module, RJ45

DN-81005-01
EAN 4016032454915



1.25 Gbps Copper SFP Module, RJ45, HP-compatible 10/100/1000Base-T, up to 100m, HP

The DIGITUS® Mini GBIC (SFP) transceiver modules offer the highest quality and reliability. The module offers a perfect opportunity for you to extend your Gigabit network switch with a free SFP Uplink Port around an additional RJ45 connection. Thanks to the hot-plug capability, you can install the module without any interruption to the network traffic or restart of the device. In addition, conformity with the MSA (Multi Source Agreement) standard provides compatibility with the current network switch manufacturers.

The plug and play extension for your network switch

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Up to 1.25 Gbps bidirectional maximum data rate

- Compliant to IEEE 802.3z Gigabit Standard
- High quality and excellent reliability
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable - installation possible while in operation
- Auto MDI/MDI-X
- Connection: 1x RJ45, CAT 5
- Distance: up to 100 m
- Operating temperature: 0 °C ~ 70 °C
- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: HP, Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.20	1.50	1.50	7.00	0.00

More images:



SFP Modules							
Product Number	SRM Code	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Version
Fast Ethernet							
DM-4001	401000000000	100 Mbps	10 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-4002	401000000002	100 Mbps	10 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-4004	401000000004	100 Mbps	10 km	LC Duplex	1310nm	0 to 70 °C	✓
Gigabit							
DM-4005	401000000005	1 Gbps	10 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-4006	401000000006	1 Gbps	10 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-4007	401000000007	1 Gbps	10 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-4008	401000000008	1 Gbps	10 km	LC Duplex	1550nm	0 to 70 °C	✓
10G							
DM-4009	401000000009	10 Gbps	10 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-4010	401000000010	10 Gbps	10 km	LC Duplex	1550nm	0 to 70 °C	✓
10G Industrial							
DM-4011	401000000011	10 Gbps	10 km	LC Duplex	1310nm	-40 to 85 °C	✓
DM-4012	401000000012	10 Gbps	10 km	LC Duplex	1550nm	-40 to 85 °C	✓
DM-4013	401000000013	10 Gbps	10 km	LC Duplex	1310nm	-40 to 85 °C	✓
DM-4014	401000000014	10 Gbps	10 km	LC Duplex	1550nm	-40 to 85 °C	✓
DM-4015	401000000015	10 Gbps	10 km	LC Duplex	1310nm	-40 to 85 °C	✓
DM-4016	401000000016	10 Gbps	10 km	LC Duplex	1550nm	-40 to 85 °C	✓